

ERTOIL SUPER SINTÉTICO DPF 5W30

DESCRIPTION



A suitable synthetic oil for all petrol and diesel vehicles of the VAG group (VW-Audi-Seat-Skoda), with or without extended maintenance (WIV). It is especially developed to meet current needs of the engines and their post-treatment gas systems (particle filters, catalytic converters etc.).

Applications

- For use in all Volkswagen* (VAG) Group petrol and diesel engines, complying with all previous Group specifications and is mandatory in models fitted with particle filter-type gas post-treatment (Dieselpartikelfilter).
- Suitable for any oil change interval recommended by the manufacturer's manual, from normal to those more extended (50,000 km or 2 years)
- Can be used in vehicles of any make that need a very high quality synthetic oil, such as those fitted with Particle Filters of the PSA Group.
- It may be used on any brand of vehicle requiring a very high quality synthetic lubricant that meets ACEA C3 and ACEA C2 specifications.
- It is also suitable for use in vehicles fitted with Mercedes Benz and BMW engines with long oil change intervals.
- It is recommended for Mitsubishi, Jeep and Dodge models that specify VW 507.00 and also for Porsche Cayenne V6 and Cayenne Diesel models.

Performance

- Due to its excellent technology, it minimises deposit formation and wear in the internal parts of the engine.
- Its maximum quality synthetic base gives very low oil consumption and, similarly, its magnificent low-temperature properties always guarantee appropriate "pumpability".
- Thanks to its low friction and viscosity, it gives excellent fuel economy characteristics.
- It maximises particle filter duration of exhaust gases, avoiding their obstruction.

SPECIFICATIONS

· ACEA C3- 10	VW 504.00 / 507.00
---------------	--------------------

TYPICAL CHARACTERISTICS

CHARACTERISTICS	ASTM STANDARD	ERTOIL SUPER SINTÉTICO 5W30 DPF
SAE Grade	---	5W-30
Density 15°C, g/cc	D-4052	0.852
Pour point, °C	D-97	-42
Viscosity at 100°C, cSt	D-445	11.65
Viscosity at 40°C, cSt	D-445	68,3
CCS Viscosity at -30°C (cP)	D-5293	<6600
Base number, mgKOH/g	D-2896	6,62
Sulphated ash, % (m/m)	D-874	≤0,8
HTHS viscosity, cP	D-4683	>3,5

HEALTH & SAFETY and ENVIRONMENT

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures together with environmental effects and disposal of used products.

The typical values of the characteristics appearing in the table are average values given for guidance purposes. These values may be modified without any prior warning.