

CEPSA AURIGA TE 55 10W30

Description



Universal multi-grade oil for tractor transmissions (UTTO) with the latest technology, fulfilling the requirements of modern agricultural equipment and suitable for use in wet brakes, hydraulic systems, clutches and torque converters.

Applications

- High oxidation stability.
- Good antiwear and Extreme Pressure properties.
- Superb protection against corrosion and rust.
- High resistance to foam formation.
- Superb fluidity at low temperatures.
- Compatible with sealing materials.

Product performance

- Reduces the formation of sludge, lacquers and varnishes.
- High load capacity.
- Perfect lubrication at all operating speeds.
- Immediate oil circulation at start-up.
- No more vibration and screeching from brakes submerged in an oil bath.

Quality Levels

- | | | |
|--|--|---|
| <ul style="list-style-type: none"> • API GL-4 • ZF TE-ML • 03E/05F/06K/17E/21F^[1] • KUBOTA UDT • VOLVO CE WB-101 | <ul style="list-style-type: none"> • Allison C3/C4 • MF CMS 1145/1143/1141/1135 • John Deere JDM J20C/D | <ul style="list-style-type: none"> • CAT TO-2 • FNHA-2C-201.00
(formerly FORD M2C-134D) • CNH MAT 3525 |
|--|--|---|

[1] ZP – ZF001200

Typical Characteristics

CHARACTERISTIC	UNITS	METHOD	AURIGA TE 55
SAE grade		J300	10W30
Density at 15°C	Kg/l	D-4052	0.8854
Flash point COC	°C	D-92	214
Pour point	°C	D-97	-32
Viscosity at 100°C	cSt	D-445	9.60
Viscosity at 40°C	cSt	D-445	56.46
Viscosity index		D-2270	155

Health & Safety and Environment

A Material Safety Data Sheet providing information on product hazards, handling precautions, first aid measures, and relevant environmental data is available for this product as per applicable legislation.

The typical values of the characteristics appearing in the table are average values given for guidance purposes only and do not constitute a guarantee. These values may be modified without any prior warning.