

# CEPSA PREMIUM AX

## Description

Monograde mineral oil lubricant.

### Applications

- Especially recommended for engines that do not require detergent properties.
- This is intended for old petrol engines working under moderate conditions and when only minimum wear and corrosion protection is required.
- Suitable for use as a general lubricant oil.
- It should not be employed in engines unless specifically recommended by the equipment manufacturer.

### Performance

- Adequate anti-wear properties.
- Good oxidation stability.
- It reduces the costs for maintenance and for the replacement of heavily run engines because of its high resistance to combustion gas action, which could filter towards the crankcase via the segments.

## Specifications

- API SB

## Typical Characteristics

CHARACTERISTICS	ASTM STANDARD	CEPSA PREMIUM AX		
		10W	30W	40W
SAE Grade				
Density 15°C, g/cc	D-4052	0.876	0.890	0.894
Flash Point (COC) °C	D-92	200	230	240
Pour Point, °C	D-97	-30	-18	-21
Viscosity at 100°C, cSt	D-445	5.9	11.45	14.5
Viscosity at 40°C, cSt	D-445	33.15	100.6	134.4
Viscosity Index	D-2270	95	95	95

## Health & Safety and Environment

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures together with environmental effects and disposal of used products.

The typical values of the characteristics appearing in the table are average values given for guidance purposes. These values may be modified without any prior warning.