



ERTOIL MULTIGRADO 20W40 DIESEL

DESCRIPTION A lubricant mineral oil for all types of atmospheric and turbo-charged diesel engines.

APPLICATIONS

- Recommended for both new and used engines with any mileage.
- For use in medium power utility and compact vehicles in both normal and demanding driving conditions.

PERFORMANCE

- Exceptional detergent/dispersant properties. Maintains all engine parts clean.
- Low volatility. Reduces oil consumption.
- Reduces friction. Eliminates moving part wear and increases useful engine life.
- Adequate fluidity. Facilitates cold starting.

SPECIFICATIONS

- API CE/SG
- CCMC D4/PD2
- M.B. 227.1
- VW 505.00

HEALTH & SAFETY AND ENVIRONMENT

Health, safety and environmental information is provided for this product in the Materials Safety Data Sheet. This gives details of potential hazards, precautions and First Aid measures together with environmental effects and disposal of used products.

TYPICAL CHARACTERISTICS

	ASTM STANDARD	ERTOIL MULTIGRADO 20W40 DIESEL
SAE GRADE	----	20W-40
Density 15°C, kg/m ³	D-4052	0,893
Flash point, COC, °C	D-92	230
Pour point, °C	D-97	-23
Viscosity at 40°C, cSt	D-445	124
Viscosity at 100°C, cSt	D-445	14
Viscosity Index	D-2270	110

The typical property values shown in the table are average figures given as a guide. They do not constitute a guarantee. Values may be modified without notice.