



# MOBILGARD 12 SERIES

## DESCRIPTION

Mobilgard 12 Series by ExxonMobil are high performance diesel engine oils developed for use in trunk piston engines operating on low sulphur distillate fuels in marine and industrial applications. They are formulated to have excellent resistance to oxidation and viscosity increase over a long period of service. They have superior water separating properties and provide excellent corrosion protection.

Mobilgard 312 and 412 meet API requirements for CF rating.

## PROPERTIES & BENEFITS

Mobilgard 12 Series is formulated with base oils having proven successful performance in diesel engines. The additive system is balanced to provide excellent resistance to thermal degradation under moderately severe operating conditions. They also provide good engine cleanliness and superior wear protection.

When used as recommended, Mobilgard 12 Series oils provide the following features and potential benefits:

Properties	Potential advantages and benefits
Excellent thermal and oxidation stability.	Extended periods between inspections, overhaul and cleaning.
Improved antiwear properties.	Reduced ring and liner wear.
Excellent TBN reserve and retention.	Increased protection against corrosive wear.
Excellent detergency/dispersancy properties.	Increased oil service life. Cleaner engines.

## APPLICATIONS

The Mobilgard 12 Series diesel engine oils are intended for use as cylinder and bearing lubricants in marine and industrial diesel engines operating on distillate fuels or light fuel blends. They are particularly effective in small bore, high speed engines in fishing fleets; in new, severe service engines; and in many types of medium speed engines. They may be used as crankcase lubricants in large crosshead type diesel engines operating on high sulphur fuels. Mobilgard 512 is recommended occasionally by some builders as running-in oil for crosshead type engines.

## TYPICAL CHARACTERISTICS

MOBILGARD 12 SERIES	312	412	512
SAE Grade	30	40	50
Specific Gravity @ 15°C	0.896	0.899	0.903
Flash Point, °C, ASTM D 92	266	272	282
Pour Point, °C, ASTM D 97	-9	-9	-9
Viscosity, ASTM D 445			
cSt, @ 40°C	108	142	219
cSt, @ 100°C	12.0	14.5	19.4
Viscosity Index, ASTM D 2270	100	100	100
TBN, mg KOH/g, ASTM D 2896	15	15	15
Sulphated Ash, wt%, ASTM D 874	2.1	2.1	2.1

## HEALTH & SAFETY

Based on available information, this product is not expected to produce adverse effects on health when used for the intended application, following the recommendations provided in the Material Safety Data Sheet (MSDS).

The typical property values shown in the table are average figures given as a guide. They do not constitute a guarantee. Values may be modified without notice.